

Shielded Power Connectors M23 Series SH Technical Data



Shell material

Machined components: die cast components: Shell plating: Cable entry:

Insulator Connector inserts:

Contacts

Contact material: Contact plating: Contact termination:

Sealing

Sealing rings: Gaskets:

Temperature

Temperature (long term) Celsius: Temperature (long term) Fahrenheit:

Mating

Mating cycles: Female coupling nuts: Male receptacles:

Protection

Protection class :

Copper-Zinc alloy (CuZn) Zinc (GD-Zn) Nickel (Ni) plated max. 18 mm

Polyamide (PA66) UL 94 V0

Copper-Zinc alloy (CuZn) Nickel (Ni) with gold (Au) passivated crimp type

Fluor rubber FKM Fluor rubber FKM


- 40 °C up to + 130°C - 40 °F up to + 266 °F

Standard min. 100 M23 screw locking/Speedcon M23 screw locking/Speedcon

IP 67 (mated) depends on which cable gland is used



All connectors with universal shielding material for different jacket and shield diameters.







Number of positions	13 Pos. (8+4+PE)			13 Pos. (4+4+4+PE)			
Number of contacts	8	4	PE	4	4	4	PE
Contact dia. (mm Ø)	1	2	2	0.8	1	2	2
Rated current at 25° (A)	8	30		3.6	8	30	
Rated voltage (V)	50	630/850		50	50	630/850	
Test voltage (V)	1,500	6,000		1,500	1,500	6,000	
Surge voltage category							
Wiring size AWG	40-17	24-12	24-12	40-20	40-17	24-12	
Wiring size AWG							

Shielded Power Connectors M23 Series SH



Shell styles 8, 9, W


SH-8ESC58A8L	SH-8ESS48A8L SH-8EPC58A8L				
page C-T-04	page C-T-05	page C-T-06			
Cable connector, straight	Cable connector, straight	Cable connector, straight			
with female coupling nut	with female coupling nut	with female coupling nut			
cable entry max. 18 mm	cable entry max. 18 mm	cable entry max. 18 mm			
female contacts + CAT	female contacts + signal	male contacts + CAT			
Speedcon	Speedcon	1/2 Speedcon			
style 8	style 8	style 8			
SH-8EPS48A8L	SH-8ESC58A9L	SH-8ESS48A9L			
page C-T-07	page C-T-08	page C-T-09			
Cable connector, straight	Cable connector, straight	Cable connector, straight			
with female coupling nut	with male thread	with male thread			
cable entry max. 18 mm	cable entry max. 18 mm	cable entry max. 18 mm			
male contacts + signal	female contacts +CAT	female + signal			
12 Speedcon style 8	style 9	style 9			
SH-8EPC58A9L	SH-8EPS48A9L	SH-8ESxxxxWA00S			
page C-T-10	page C-T-11	page C-T-12			
Cable connector, straight	Cable connector, straight	Panel connector, straight			
with male thread	with male thread	with male thread			
cable entry max. 18 mm	cable entry max. 18 mm	flat design, axial O-ring			
male contacts + CAT	mal contacts + signal	square flange 26 mm			
style 9	style 9	style W			

Shielded Power Connectors M23 Series SH Shell styles W, AC, AD




<u></u>	Shell styles W, AC, AD						
SH-8EPxxxxWA00S	SH-8EPxxxxWA00S	SH-8EPxxxxWA00S					
page C-T-13	page C-T-14	page C-T-15					
Panel connector, straight	Panel connector, straight	Panel connector, straight					
with male thread	with male thread	with male thread					
flat design, axial O-ring	flat design, axial O-ring	flat design, axial O-ring					
square flange 26 mm 🗌	square flange 26 mm 🗌	square flange 26 mm 🗌					
style W	style W	style W					
	<u> </u>	-					
SH-8ESxxxxAD/AC	SH-8ESxxxxAD/AC	SH-8EPxxxxAD/AC					
page C-T-16	page C-T-17	page C-T-18					
Panel connector, angled	Panel connector, angled	Panel connector, angled					
with male thread	with male thread	with male thread					
angled design, axial O-ring	angled design, axial O-ring	angled design, axial O-ring square flange 26/28 mm □					
square flange 26/28 mm 🗌	square flange 26/28 mm 🗌						
style AD/AC	style AD/AC	style AD/AC					
SH-8EPxxxxAD/AC page C-T-19							
Panel connector, angled with male thread angled design, axial O-ring square flange 26/28 mm 🗌							
style AD/AC							





















71,2 M23x1 028 all with integrated strain relief Caps and accessories: pages B-H-01... We also deliver as a connector set. Mounting tools: pages B-E-01... Connector with crimp insert - and Assembly instructions: page B-D-30 the contacts are separate included. Please ask for P/N Crimp tools for contacts: pages B-B-02B Crimp contacts: pages B-C-62 Part Number SH-E S С 5 8 8 Α 9 L Х Х Х Cable entries..... **S** 7.5 - 18 mm D 1 M23 cable connector, hybrid В 4 **S** 7.5 - 9 mm 1 PE contact (center) female 2 mm 4 Power contacts 3 **S** 9 - 12 mm female 2 mm В 1 mm 4 Signal contacts female 2 **S** 12 - 15 mm В 0.8 mm 4 Data contacts (CAT) female **S** 15 - 18 mm B 1



71,2 M23x1 028 all with integrated strain relief We also deliver as a connector set. Caps and accessories: pages B-H-01... Mounting tools: pages B-E-01... Connector with crimp insert - and Assembly instructions: page B-D-30 the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-E S S 4 8 8 Α 9 L Х Х Х Cable entries..... **S** 7.5 - 18 mm D 1 M23 cable connector, hybrid **S** 7.5 - 9 mm В 4 1 PE contact (center) female 2 mm 4 Power contacts female 3 **S** 9 - 12 mm 2 mm В 1 mm 8 Signal contacts female 2 **S** 12 - 15 mm В **S** 15 - 18 mm B 1




71,2 M23x1 028 all with integrated strain relief We also deliver as a connector set. Caps and accessories: pages B-H-01... Mounting tools: pages B-E-01... Connector with crimp insert - and Assembly instructions: page B-D-30 the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-E Ρ С 5 8 8 Α 9 L Х Х Х Cable entries..... **S** 7.5 - 18 mm D L M23 cable connector, hybrid В 4 **S** 7.5 - 9 mm 1 PE contact (center) male 2 mm 4 Power contacts 3 **S** 9 - 12 mm male 2 mm В 1 mm 4 Signal contacts male 2 **S** 12 - 15 mm 0.8 mm В 4 Data contacts (CAT) male **S** 15 - 18 mm B 1




71,2 M23x1 028 all with integrated strain relief We also deliver as a connector set. Caps and accessories: pages B-H-01... **Mounting tools:** pages B-E-01... Connector with crimp insert - and Assembly instructions: page B-D-30 the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-Е Ρ S 4 8 8 Α 9 Cable entries..... L Х Х Х **S** 7.5 - 18 mm D L M23 cable connector, hybrid **S** 7.5 - 9 mm В 4 1 PE contact (center) male 2 mm 4 Power contacts 3 **S** 9 - 12 mm male 2 mm В 1 mm 8 Signal contacts male 2 **S** 12 - 15 mm В **S** 15 - 18 mm B 1





















54 40 socket version: dimension A = 0 mm Pin version: dimension A = 4.7 mm nstallation dimension: **22,6** Ø20 032 22 4xØ3.2 8 We also deliver as a connector set. Caps and accessories: pages B-H-01... **Mounting tools:** pages B-E-01... Connector with crimp insert - and Assembly instructions: page n/a the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-8 Ε S С 5 8 Α Х Х Х Х Х 0 square flange Α D 0 S M23 cable connector, hybrid angled angled with square flange 26 x 26 mm 1 PE contact (center) with axial O-ring female 2 mm 4 Power contacts female 2 mm С 0 0 **S** square flange 4 Signal contacts female 1 mm Α angled 0.8 mm 4 Data contacts (CAT) female 28 x 28 mm with axial O-ring



54 40 Pin version: dimension A = 4.7 mm, socket version: dimension A = 0 mm nstallation dimension: **22,6** Ø20 032 22 4xØ3.2 18 We also deliver as a connector set. Caps and accessories: pages B-H-01... **Mounting tools:** pages B-E-01... Connector with crimp insert - and Assembly instructions: page n/a the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-8 Ε S S 4 8 Α Х Х Х Х Х 0 square flange Α D 0 S M23 cable connector, hybrid angled angled with square flange 26 x 26 mm 1 PE contact (center) with axial O-ring female 2 mm 4 Power contacts female 2 mm С 0 0 **S** square flange 8 Signal contacts female 1 mm Α angled 28 x 28 mm with axial O-ring



54 40 socket version: dimension A = 0 mm Pin version: dimension A = 4.7 mm nstallation dimension: **22,6** Ø20 032 22 4xØ3.2 8 We also deliver as a connector set. Caps and accessories: pages B-H-01... **Mounting tools:** pages B-E-01... Connector with crimp insert - and Assembly instructions: page n/a the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-8 Ε Ρ С 5 8 Α Х Х Х Х Х 0 square flange Α D 0 S M23 cable connector, hybrid angled angled with square flange 26 x 26 mm 1 PE contact (center) with axial O-ring male 2 mm 4 Power contacts male 2 mm С 0 0 **S** square flange 4 Signal contacts 1 mm Α male angled 0.8 mm 4 Data contacts (CAT) male 28 x 28 mm with axial O-ring



54 40 socket version: dimension A = 0 mm Pin version: dimension A = 4.7 mm nstallation dimension: **22,6** Ø20 032 22 4xØ3.2 18 We also deliver as a connector set. Caps and accessories: pages B-H-01... **Mounting tools:** pages B-E-01... Connector with crimp insert - and Assembly instructions: page n/a the contacts are separate included. Crimp tools for contacts: pages B-B-02B Please ask for P/N Crimp contacts: pages B-C-62 Part Number SH-8 Ε Ρ S 8 4 Α Х Х Х Х Х 0 square flange Α D 0 S M23 cable connector, hybrid angled angled with square flange 26 x 26 mm 1 PE contact (center) with axial O-ring male 2 mm 4 Power contacts male 2 mm С 0 0 **S** square flange 8 Signal contacts 1 mm Α male angled 28 x 28 mm with axial O-ring